





SMART⁺ WIFI FLOOD



	EAN	W	lm	K		 (°C)	V~	mA	Hz		PF
SMART OUTD WIFI FLOOD 10W RGBW DG	4058075474604	10	630	3000	0.012769	-20...+40	220-240	45	50/60	100	>0.9
SMART OUTD WIFI FLOOD 20W RGBW DG	4058075474628	20	1260	3000	0.012769	-20...+40	220-240	90	50/60	100	>0.9
SMART OUTD WIFI FLOOD 30W RGBW DG	4058075474642	30	2190	3000	0.024948	-20...+40	220-240	140	50/60	100	>0.9
SMART OUTD WIFI FLOOD 50W DIM DG	4058075474666	50	4250	3000	0.035532	-20...+40	220-240	220	50/60	100	>0.9



 **380 g**
4058075474604


 **380 g**
4058075474628

 **650 g**
4058075474642

 **1000 g**
4058075474666

2x  1x 


2x  **not included**

	W	H	L
10W	125	28	152
20W	125	28	152
30W	168	30	209
50W	200	36	237

1






ON


OFF


2



500mm (10W-50W)


3









Max.: 2.5N.m

4



max. 5m
(10-50W)





RoHS IP65

C10449057
G11099585V2
15.07.2020



LEDVANCE GmbH
Steinerne Furt 62
86167 Augsburg, Germany
www.ledvance.com